



Hybrid consumer unit L · flush-mounted · door: anthracite

Two-storey house: consumer unit and multimedia section in one enclosure, with spare space.

PLN 7,097.10

incl. 23% VAT · PLN 5,770.00 excl. VAT · excluding delivery

Some items have a preliminary price (new in our range) — we will confirm it when we check your order.

Enclosure L with 4 DIN rows (20 circuits, 3 RCDs, T1+T2 surge protection) and a multimedia section below a partition: 24 × RJ45 patch panel, space for the provider's router and terminal, 230 V power strip on a dedicated circuit.

MOUNTING AND DIMENSIONS

Mounting	flush-mounted — back box built into the wall, frame with door
Wall opening	320 × 995 mm, depth 100 mm
Minimum wall thickness	120 mm
Frame with door (visible)	350 × 1025 mm

Approximate dimensions — we confirm them against the data sheet of the selected enclosure in the order confirmation (before you cut the recess).

CONTENTS

DIN rail 43 / 48 modules · 4 rows · enclosure L

Main switch, surge protection device, phase indicators, N/PE terminal bars	9 mod.
4-pole residual current devices (RCDs) × 3	12 mod.
Circuit breakers (MCBs) × 20 (sockets, lighting, appliances)	20 mod.
Flush-mounted enclosure (back box for building into the wall, frame with door)	—
Door: anthracite	—
Multimedia section — hybrid enclosure with a partition separating it from the 230 V section	—
Patch panel 24 × RJ45	—
230 V power strip for network power supplies (4 sockets)	—
Dedicated protected 230 V socket circuit (RCBO)	2 mod.

SPECIFICATIONS

Door: **Anthracite — Graphite powder coating — for dark interiors and ceilings** DIN rail **43 used of 48 (spare 5)**

Circuits: **20 (max. 26 in this enclosure)**

Residual current devices (RCDs): **3 × 4-pole, 30 mA**

Surge protection device (SPD): **T1+T2**

Multimedia section: **behind a partition from the 230 V section: patch panel**

Lead time: 5–10 working days from receipt of the deposit.

Included: wiring diagram, circuit chart, test report, EU declaration of conformity, 24-month warranty. Built to EN 61439-3 (PN-EN 61439-3). Technical documents are issued in Polish.

<https://svalcon.broke-it.net/en/products/hybrid-1?mounting=flush>

