



# Hybrid consumer unit L · 8-port patch panel · PoE switch

Two-storey house: consumer unit and multimedia section in one enclosure, with spare space.

## PLN 6,814.20

incl. 23% VAT · PLN 5,540.00 excl. VAT · excluding delivery

Some items have a preliminary price (new in our range) — we will confirm it when we check your order.

Enclosure L with 4 DIN rows (20 circuits, 3 RCDs, T1+T2 surge protection) and a multimedia section below a partition: 24 × RJ45 patch panel, space for the provider's router and terminal, 230 V power strip on a dedicated circuit.

### MOUNTING AND DIMENSIONS

Mounting **surface-mounted — enclosure on the wall**

Enclosure dimensions **300 × 975 × 115 mm (W × H × D)**

Approximate dimensions — we confirm them against the data sheet of the selected enclosure in the order confirmation (before you cut the recess).



### CONTENTS

DIN rail 43 / 48 modules · 4 rows · enclosure L

|                                                                                             |         |
|---------------------------------------------------------------------------------------------|---------|
| Main switch, surge protection device, phase indicators, N/PE terminal bars                  | 9 mod.  |
| 4-pole residual current devices (RCDs) × 3                                                  | 12 mod. |
| Circuit breakers (MCBs) × 20 (sockets, lighting, appliances)                                | 20 mod. |
| Door: anthracite                                                                            | —       |
| Multimedia section — hybrid enclosure with a partition separating it from the 230 V section | —       |
| Patch panel 8 × RJ45                                                                        | —       |
| 230 V power strip for network power supplies (4 sockets)                                    | —       |
| Dedicated protected 230 V socket circuit (RCBO)                                             | 2 mod.  |
| 8-port PoE switch                                                                           | —       |

### SPECIFICATIONS

Door: **Anthracite — Graphite powder coating — for dark interiors and ceilings** Standard ceiling: **43 used of 48 (spare 5)**

Circuits: **20 (max. 26 in this enclosure)**

Residual current devices (RCDs): **3 × 4-pole, 30 mA**

Surge protection device (SPD): **T1+T2**

Multimedia section: **behind a partition from the 230 V section: patch panel**

Lead time: 5–10 working days from receipt of the deposit.

Included: wiring diagram, circuit chart, test report, EU declaration of conformity, 24-month warranty. Built to EN 61439-3 (PN-EN 61439-3). Technical documents are issued in Polish.

<https://svalcon.broke-it.net/en/products/hybrid-1>