



Hybrid consumer unit M · flush-mounted · 8-port patch panel

Single-storey house: power and internet in one enclosure — the consumer unit at the top, the multimedia section below a partition

PLN 5,805.60

incl. 23% VAT · PLN 4,720.00 excl. VAT · excluding delivery

Some items have a preliminary price (new in our range) — we will confirm it when we check your order.

Enclosure M with 3 DIN rows (14 circuits, 2 RCDs, T1+T2 surge protection) and a multimedia section below a partition: 12 × RJ45 patch panel, space for the provider's router and terminal, 230 V power strip on a dedicated circuit.

MOUNTING AND DIMENSIONS

Mounting	flush-mounted — back box built into the wall, frame with door
Wall opening	320 × 820 mm, depth 100 mm
Minimum wall thickness	120 mm
Frame with door (visible)	350 × 850 mm

Approximate dimensions — we confirm them against the data sheet of the selected enclosure in the order confirmation (before you cut the recess).

CONTENTS

DIN rail 33 / 36 modules · 3 rows · enclosure M

Main switch, surge protection device, phase indicators, N/PE terminal bars	9 mod.
4-pole residual current devices (RCDs) × 2	8 mod.
Circuit breakers (MCBs) × 14 (sockets, lighting, appliances)	14 mod.
Flush-mounted enclosure (back box for building into the wall, frame with door)	—
Door: tinted glass	—
Multimedia section — hybrid enclosure with a partition separating it from the 230 V section	—
Patch panel 8 × RJ45	—
230 V power strip for network power supplies (4 sockets)	—
Dedicated protected 230 V socket circuit (RCBO)	2 mod.

SPECIFICATIONS

Door: **Tinted glass — White frame with tinted glass — you can see the LEDs and devices at a glance** without opening the door.

Circuits: **14 (max. 18 in this enclosure)**

Residual current devices (RCDs): **2 × 4-pole, 30 mA**

Surge protection device (SPD): **T1+T2**

Multimedia section: **behind a partition from the 230 V section: patch panel**

Lead time: 5–10 working days from receipt of the deposit.

Included: wiring diagram, circuit chart, test report, EU declaration of conformity, 24-month warranty. Built to EN 61439-3 (PN-EN 61439-3). Technical documents are issued in Polish.

<https://svalcon.broke-it.net/en/products/hybrid-m?mounting=flush>

