



# Hybrid consumer unit M · PoE switch · door: oak

Single-storey house: power and internet in one enclosure — the consumer unit at the top, the multimedia section below a partition

## PLN 6,063.90

incl. 23% VAT · PLN 4,930.00 excl. VAT · excluding delivery

Some items have a preliminary price (new in our range) — we will confirm it when we check your order.

Enclosure M with 3 DIN rows (14 circuits, 2 RCDs, T1+T2 surge protection) and a multimedia section below a partition: 12 × RJ45 patch panel, space for the provider's router and terminal, 230 V power strip on a dedicated circuit.

### MOUNTING AND DIMENSIONS

Mounting

**surface-mounted — enclosure on the wall**

Enclosure dimensions

**300 × 800 × 115 mm (W × H × D)**

Approximate dimensions — we confirm them against the data sheet of the selected enclosure in the order confirmation (before you cut the recess).



### CONTENTS

DIN rail 33 / 36 modules · 3 rows · enclosure M

|                                                                                             |         |
|---------------------------------------------------------------------------------------------|---------|
| Main switch, surge protection device, phase indicators, N/PE terminal bars                  | 9 mod.  |
| 4-pole residual current devices (RCDs) × 2                                                  | 8 mod.  |
| Circuit breakers (MCBs) × 14 (sockets, lighting, appliances)                                | 14 mod. |
| Door: oak                                                                                   | —       |
| Multimedia section — hybrid enclosure with a partition separating it from the 230 V section | —       |
| Patch panel 12 × RJ45                                                                       | —       |
| 230 V power strip for network power supplies (4 sockets)                                    | —       |
| Dedicated protected 230 V socket circuit (RCBO)                                             | 2 mod.  |
| 8-port PoE switch                                                                           | —       |

### SPECIFICATIONS

Door: **Oak — Wood-effect veneer in natural oak.**

Circuits: **14 (max. 18 in this enclosure)**

Surge protection device (SPD): **T1+T2**

DIN modules: **33 used of 36 (spare 3)**

Residual current devices (RCDs): **2 × 4-pole, 30 mA**

Multimedia section: **behind a partition from the 230 V section: patch panel**

Lead time: 5–10 working days from receipt of the deposit.

Included: wiring diagram, circuit chart, test report, EU declaration of conformity, 24-month warranty. Built to EN 61439-3 (PN-EN 61439-3). Technical documents are issued in Polish.

<https://svalcon.broke-it.net/en/products/hybrid-m>