



Consumer unit L · Standard · flush-mounted · door: anthracite

Two-storey house or a house of 150–250 m² — separate circuits for each floor, the garage and the garden — without solar PV

PLN 4,895.40

incl. 23% VAT · PLN 3,980.00 excl. VAT · excluding delivery

Some items have a preliminary price (new in our range) — we will confirm it when we check your order.

22 circuits. Circuits for sockets, lighting and appliances, 4-pole RCDs and a surge protection device. Enclosure L, 4 rows of DIN rail.

MOUNTING AND DIMENSIONS

Mounting	flush-mounted — back box built into the wall, frame with door
Wall opening	320 × 695 mm, depth 100 mm
Minimum wall thickness	120 mm
Frame with door (visible)	350 × 725 mm

Approximate dimensions — we confirm them against the data sheet of the selected enclosure in the order confirmation (before you cut the recess).



CONTENTS

DIN rail 43 / 48 modules · 4 rows · enclosure L

Main switch, surge protection device, phase indicators, N/PE terminal bars	9 mod.
4-pole residual current devices (RCDs) × 3	12 mod.
Circuit breakers (MCBs) × 22 (sockets, lighting, appliances)	22 mod.
Flush-mounted enclosure (back box for building into the wall, frame with door)	—
Door: anthracite	—

SPECIFICATIONS

Door: Anthracite — Graphite powder coating — for dark interiors and ceilings	54 used of 48 (spare 5)
Circuits: 22 (max. 26 in this enclosure)	Residual current devices (RCDs): 3 × 4-pole, 30 mA
Surge protection device (SPD): T1+T2	

Lead time: 5–10 working days from receipt of the deposit.

Included: wiring diagram, circuit chart, test report, EU declaration of conformity, 24-month warranty. Built to EN 61439-3 (PN-EN 61439-3). Technical documents are issued in Polish.

<https://svalcon.broke-it.net/en/products/l-standard?mounting=flush>