



Consumer unit M · Standard

Single-storey house up to about 150 m² — without solar PV or EV charger, replacing an old board with a new one with surge p

PLN 3,062.70

incl. 23% VAT · PLN 2,490.00 excl. VAT · excluding delivery

16 circuits. Circuits for sockets, lighting and appliances, 4-pole RCDs and a surge protection device. Enclosure M, 3 rows of DIN rail.

MOUNTING AND DIMENSIONS

Mounting **surface-mounted — enclosure on the wall**

Enclosure dimensions **300 × 550 × 115 mm (W × H × D)**

Approximate dimensions — we confirm them against the data sheet of the selected enclosure in the order confirmation (before you cut the recess).



CONTENTS

DIN rail 33 / 36 modules · 3 rows · enclosure M

Main switch, surge protection device, phase indicators, N/PE terminal bars	9 mod.
4-pole residual current devices (RCDs) × 2	8 mod.
Circuit breakers (MCBs) × 16 (sockets, lighting, appliances)	16 mod.

SPECIFICATIONS

DIN modules: **33 used of 36 (spare 3)**

Circuits: **16 (max. 18 in this enclosure)**

Residual current devices (RCDs): **2 × 4-pole, 30 mA**

Surge protection device (SPD): **T1+T2**

Lead time: 5–10 working days from receipt of the deposit.

Included: wiring diagram, circuit chart, test report, EU declaration of conformity, 24-month warranty. Built to EN 61439-3 (PN-EN 61439-3). Technical documents are issued in Polish.

<https://svalcon.broke-it.net/en/products/m-standard>