



# Consumer unit M · Standard · flush-mounted

Single-storey house up to about 150 m<sup>2</sup> — without solar PV or EV charger, replacing an old board with a new one with surge p

## PLN 3,493.20

incl. 23% VAT · PLN 2,840.00 excl. VAT · excluding delivery

Some items have a preliminary price (new in our range) — we will confirm it when we check your order.

16 circuits. Circuits for sockets, lighting and appliances, 4-pole RCDs and a surge protection device. Enclosure M, 3 rows of DIN rail.

### MOUNTING AND DIMENSIONS

|                           |                                                                      |
|---------------------------|----------------------------------------------------------------------|
| Mounting                  | <b>flush-mounted — back box built into the wall, frame with door</b> |
| Wall opening              | <b>320 × 570 mm, depth 100 mm</b>                                    |
| Minimum wall thickness    | <b>120 mm</b>                                                        |
| Frame with door (visible) | <b>350 × 600 mm</b>                                                  |

Approximate dimensions — we confirm them against the data sheet of the selected enclosure in the order confirmation (before you cut the recess).



### CONTENTS

DIN rail 33 / 36 modules · 3 rows · enclosure M

|                                                                                |         |
|--------------------------------------------------------------------------------|---------|
| Main switch, surge protection device, phase indicators, N/PE terminal bars     | 9 mod.  |
| 4-pole residual current devices (RCDs) × 2                                     | 8 mod.  |
| Circuit breakers (MCBs) × 16 (sockets, lighting, appliances)                   | 16 mod. |
| Flush-mounted enclosure (back box for building into the wall, frame with door) | —       |

### SPECIFICATIONS

|                                                           |                                                 |
|-----------------------------------------------------------|-------------------------------------------------|
| DIN modules: <b>33 used of 36 (spare 3)</b>               | Circuits: <b>16 (max. 18 in this enclosure)</b> |
| Residual current devices (RCDs): <b>2 × 4-pole, 30 mA</b> | Surge protection device (SPD): <b>T1+T2</b>     |

Lead time: 5–10 working days from receipt of the deposit.

Included: wiring diagram, circuit chart, test report, EU declaration of conformity, 24-month warranty. Built to EN 61439-3 (PN-EN 61439-3). Technical documents are issued in Polish.

<https://svalcon.broke-it.net/en/products/m-standard?mounting=flush>