



Multimedia enclosure M · flush-mounted · 8-port patch

Single-storey house: space for the provider's router and terminal, up to 12 network sockets.

PLN 1,992.60

incl. 23% VAT · PLN 1,620.00 excl. VAT · excluding delivery

Some items have a preliminary price (new in our range) — we will confirm it when we check your order.

Perforated mounting plate with space for two devices, a 12 × RJ45 patch panel, a 230 V power strip for power supplies on a dedicated protected circuit, ventilation. Optional PoE switch for cameras and access points.

MOUNTING AND DIMENSIONS

Mounting	flush-mounted — back box built into the wall, frame with door
Wall opening	380 × 540 mm, depth 100 mm
Minimum wall thickness	120 mm
Frame with door (visible)	410 × 570 mm

Approximate dimensions — we confirm them against the data sheet of the selected enclosure in the order confirmation (before you cut the recess).



CONTENTS

DIN rail 2 / 6 modules · 1 row · enclosure M

Multimedia enclosure M (perforated mounting plate, ventilation, space for 2 provider devices)	—
Flush-mounted enclosure (back box for building into the wall, frame with door)	—
Patch panel 8 × RJ45	—
230 V power strip for network power supplies (4 sockets)	—
Dedicated protected 230 V socket circuit (RCBO)	2 mod.

SPECIFICATIONS

Patch panel: **8 × RJ45, with labelled ports**

Provider devices: **space for 2 (router, fibre terminal) — supplied by your installer**

Lead time: 5–10 working days from receipt of the deposit.

Included: wiring diagram, circuit chart, test report, EU declaration of conformity, 24-month warranty. Built to EN 61439-3 (PN-EN 61439-3). Technical documents are issued in Polish.

<https://svalcon.broke-it.net/en/products/multimedia-m?mounting=flush>