



Consumer unit S · EV · flush-mounted

Flat or small house up to about 80 m² with one kitchen, with an electric vehicle (EV): a dedicated 11 kW charger circuit with a

PLN 4,956.90

incl. 23% VAT · PLN 4,030.00 excl. VAT · excluding delivery

Some items have a preliminary price (new in our range) — we will confirm it when we check your order.

10 circuits. An 11 kW EV charger on a dedicated circuit with a Type B RCD — a requirement for chargers. The devices don't fit in enclosure S, so the consumer unit is built in enclosure M (3 rows of DIN rail) — the same number of circuits, more spare space.

MOUNTING AND DIMENSIONS

Mounting	flush-mounted — back box built into the wall, frame with door
Wall opening	320 × 570 mm, depth 100 mm
Minimum wall thickness	120 mm
Frame with door (visible)	350 × 600 mm

Approximate dimensions — we confirm them against the data sheet of the selected enclosure in the order confirmation (before you cut the recess).



CONTENTS

DIN rail 34 / 36 modules · 3 rows · enclosure M

Main switch, surge protection device, phase indicators, N/PE terminal bars	9 mod.
4-pole residual current devices (RCDs) × 2	8 mod.
Circuit breakers (MCBs) × 10 (sockets, lighting, appliances)	10 mod.
Flush-mounted enclosure (back box for building into the wall, frame with door)	—
EV charging — 11 kW	7 mod.
Type B RCD for the charger	—

SPECIFICATIONS

DIN modules: 34 used of 36 (spare 2)	Circuits: 10 (max. 18 in this enclosure)
Residual current devices (RCDs): 2 × 4-pole, 30 mA	Surge protection device (SPD): T1+T2

Lead time: 5–10 working days from receipt of the deposit.

Included: wiring diagram, circuit chart, test report, EU declaration of conformity, 24-month warranty. Built to EN 61439-3 (PN-EN 61439-3). Technical documents are issued in Polish.

<https://svalcon.broke-it.net/en/products/s-ev?mounting=flush>